



Jacques M. Glaze

Professional Land Surveying

Reg. Surveyor # 6817

Marion, Ohio

SURVEY DESCRIPTION

COMBINED PARCELS "B" and "C"

Situated in the Township of Antrim, County of Wyandot, State of Ohio, and being a part of the West Half of the Northwest Quarter Section Four (4) of Township Four (4) South, Range Fifteen (15) East, and being more particularly bounded and described as follows;

Commencing at a stone and monument box found at the southeast corner of the west half of the northwest quarter section four (4) aforesaid, said point also being in the centerline of Township Highway Seventy-two (72) and in the south line of the northwest quarter section four (4);

Thence south $89^{\circ}01'27''$ west along and with the aforesaid centerline of Twp. Hwy. 72 and the south line of the northwest quarter section 4, a distance of 195.00 feet to a railroad spike set at the place of beginning;

Thence continuing south $89^{\circ}01'27''$ west along and with the aforesaid centerline of Twp. Hwy. 72 and the south line of the northwest quarter section 4, passing over a railroad spike set at 195.00 feet, a distance of 390.00 feet to a railroad spike set;

Thence north $00^{\circ}12'13''$ west, parallel with the east line of the west half of the northwest quarter section 4, passing over an iron pin set at 30.00 feet, a distance of 250.00 feet to an iron pin set;

Thence north $89^{\circ}01'27''$ east parallel with the centerline of Twp. Hwy. 72 and the south line of the northwest quarter section 4, passing over an iron pin set at 195.00 feet, a distance of 390.00 feet to an iron pin set;

Thence south $00^{\circ}12'13''$ east parallel with the east line of the west half of the northwest quarter section 4, passing over an iron pin set at 220.00 feet, a distance of 250.00 feet to the place of beginning.

containing 2.238 acres of land more or less and subject to legal highways, easements, and restrictions of record.

The foregoing description was prepared from an actual field survey performed on October 31st, 1992 by Jacques M. Glaze, registered surveyor number 6817, and field assistant Dale A. Vance.

All points designated "iron pin set" have a 5/8 inch diameter rebar in place with a yellow plastic cap bearing the inscription "Jacques Glaze S-6817."

Bearing reference was assumed north as shown on the accompanying plat of survey dated November 1st, 1992 and prepared by Jacques M. Glaze.

Prior deed reference Volume 191; page 749 on file in the Wyandot County Recorder's Office.

Jacques M. Glaze

PARCEL "A"
SURVEY DESCRIPTION

Situated in the Township of Antrim, County of Wyandot, State of Ohio, and being a part of the West Half of the Northwest Quarter Section Four (4) of Township Four (4) South, Range Fifteen (15) East, and being more particularly bounded and described as follows:

Beginning at a Stone and Monument Box found at the Southeast Corner of the West Half of the Northwest Quarter Section Four (4) aforesaid, said point also being in the Centerline of Township Highway Seventy-Two (72) and in the South Line of the Northwest Quarter Section Four (4);

Thence South $89^{\circ}01'27''$ West along and with the aforesaid Centerline of Twp. Hwy. 72 and the South Line of the Northwest Quarter Section 4, a distance of 195.00 feet to a Railroad Spike set;

Thence North $00^{\circ}12'13''$ West and parallel with the East Line of the West Half of the Northwest Quarter Section 4, passing over an Iron Pin set at 30.00 feet, a distance of 250.00 feet to an Iron Pin set;

Thence North $89^{\circ}01'27''$ East and parallel with the Centerline of Twp. Hwy. 72 and the South Line of the Northwest Quarter Section 4, a distance of 195.00 feet to an Iron Pin set in the East Line of the West Half of the Northwest Quarter Section 4;

Thence South $00^{\circ}12'13''$ East along and with the East Line of the West Half of the Northwest Quarter Section 4 and passing over an Iron Pipe previously set at 221.00 feet, a distance of 250.00 feet to the Place of Beginning.

Containing 1.119 Acres of land more or less and subject to legal highways, easements, and restrictions of record.

The foregoing description was prepared from an actual field survey performed on October 31st, 1992 by Jacques M. Glaze, Registered Surveyor No. 6817 and field assistant Dale A. Vance.

All points designated "Iron Pin Set" have a 5/8 inch diameter rebar in place with a yellow plastic cap bearing the inscription "Jacques M. Glaze S-6817."

Bearing Reference was assumed North as shown on the accompanying plat of survey dated November 1st, 1992 and prepared by Jacques M. Glaze.

Prior Deed reference Volume 191, Page 749 on file in the Wyandot County Recorder's Office.

REFERENCE SURVEY VOL. 8
PAGE 83 IN THE TAX MAP OFFICE