

**LEGAL DESCRIPTION OF A 37.442 ACRE
PARCEL FOR ENVIRITE CORPORATION**

Being a parcel of land situated in part of the northwest and southwest quarters of section 35, T-1-S, R-13-E, Crawford Township, Wyandot County, Ohio and further described as follow:

Commencing at a found iron pipe in a monument box marking the northeast corner of the northwest quarter;

thence S 90° 00' 00" W along the centerline of County Highway 29, a distance of 899.36 feet to a set P-K nail and being the POINT OF BEGINNING;

thence S 01° 07' 18" W, a distance of 2833.04 feet to a set iron rod, passing a set iron rod a distance of 30.01 feet;

thence S 89° 36' 38" W, a distance of 703.03 feet to a set P-K nail on the centerline of SR 199, passing a set iron rod a distance of 653.66 feet;

thence N 24° 40' 50" W along said centerline, a distance of 558.64 feet to a set P-K nail;

thence N 79° 01' 00" E, a distance of 355.79 feet to a found iron pipe, passing a found iron pipe a distance of 22.63 feet;

thence N 01° 30' 18" E, a distance of 437.02 feet to a set iron rod, passing a found iron pipe a distance of 427.12 feet;

thence N 89° 54' 38" E, a distance of 44.60 feet to a set iron rod;

thence N 01° 21' 38" E, a distance of 1405.81 feet to a set iron rod;

thence N 85° 00' 48" E, a distance of 248.76 feet to a point referenced by a found iron pipe located 1.0 foot east and 0.2 feet north;

thence N 01° 38' 43" W, a distance of 398.07 feet to a found railroad spike on the centerline of County Highway 29, passing a set iron rod a distance of 368.06 feet;

thence N 90° 00' 00" E along said centerline, a distance of 316.61 feet to the POINT OF BEGINNING.

Containing in all 37.442 acres of land, more or less, of which 35.219 acres are located in the northwest quarter and 2.223 acres are located in the southwest quarter and being subject to all legal highways and easements of record.

Bearings are assumed for angular measurement only.

(Parcel 3)

This legal description is based upon a survey performed by Victor B. Koehler, P.S., #7457, in March, 1995.

95009-S (015)

Parcel 3

**LEGAL DESCRIPTION OF A 31.454 ACRE
PARCEL FOR ENVIRITE CORPORATION**

Being a parcel of land situated in part of the northeast quarter of section 35, T-1-S, R-13-E, Crawford Township, Wyandot County, Ohio, and further described as follows:

Commencing at a found iron pipe in a monument box marking the northeast corner of the northwest quarter;

thence N 89° 55' 45" E along the centerline of County Highway 29, a distance of 250.00 feet to a set P-K nail and being the POINT OF BEGINNING;

thence continuing N 89° 55' 45" E along said centerline, a distance of 625.42 feet to a found railroad spike;

thence S 01° 17' 10" E, a distance of 1615.77 feet to a found iron rod, passing a found iron rod a distance of ~~25.00~~ feet; *30.01 per Dean Leonard 08-29-06*

thence S 89° 34' 28" W, a distance of 864.30 feet to a found iron rod;

thence N 01° 40' 33" W, a distance of 1471.39 feet to a set iron rod;

thence N 89° 55' 45" E, a distance of 250.00 feet to a point, passing a set iron rod a distance of ~~245.00~~ feet; *244.99 per Dean Leonard 08-29-06*

thence N 01° 40' 33" W, a distance of 150.00 feet to the POINT OF BEGINNING, passing a set iron rod a distance of 119.99 feet,

Containing in all 31.454 acres of land, more or less, and being subject to all legal highways and easements of record.

Bearings are assumed for angular measurement. only.

This legal description is based upon a survey performed by Victor B. Koehler, P.S., #7457, in March, 1995

95009-S (015)

Parcel 1

(Parcel 1)

Vol. D PAGE 99

**LEGAL DESCRIPTION OF A 62.898 ACRE
PARCEL FOR ENVIRITE CORPORATION**

Being a parcel of land situated in part of the northwest and southwest quarters of section 35, T-1-S, R-13-E, Crawford Township, Wyandot County, Ohio, and further described as follows:

Commencing at a found iron pipe in a monument box marking the northeast corner of the northwest quarter and being the POINT OF BEGINNING;

thence S $01^{\circ} 40' 33''$ E, a distance of 2694.76 feet to a found 8" wood post located at the center of said section, passing a set iron rod a distance of 150.00 feet and a found iron rod a distance of 1621.39 feet;

thence S $02^{\circ} 45' 07''$ E, a distance of 131.97 feet to a set iron rod;

thence S ~~89~~ $09^{\circ} 36' 38''$ W, a distance of 1040.00 feet to a set iron rod;

thence N $01^{\circ} 07' 18''$ E, a distance of 2833.04 feet to a set P-K nail on the centerline of County Highway 29, passing a set iron rod a distance of 2803.03 feet;

thence N $90^{\circ} 00' 00''$ E along said centerline, a distance of 899.36 feet to the POINT OF BEGINNING.

Containing in all 62.898 acres of land, more or less, of which 59.763 acres are located in the northwest quarter and 3.135 acres are located in the southwest quarter and being subject to all legal highways and easements of record.

Bearings are assumed for angular measurement only.

This legal description is based upon a survey performed by Victor B. Koehler, P.S., #7457, in March, 1995.

95009-S (015)

Parcel 2

(Parcel 2)