


VOL 7-185

## TOWNSHIP HIGHWAY 49 60' R/W

N 90° 00' 00" E (ASSUMED) 386.73' (M)

S 90° 00' 00" W 1310.23' (M)

1" = 50'  
SCALE  
50 0 50  
FEET

## REFERENCES

DEED VOLUME AND PAGE AS SHOWN

WYANDOT COUNTY CORNERSTONE REFERENCES

SURVEY FOR: RICK SCHECK  
LOCATED IN THE NE. 1/4 OF SECTION 29,  
SALEM TOWNSHIP, T-2-S, R-13-E,  
WYANDOT COUNTY, OHIOHANK AND ASSOCIATES, INC.  
ENGINEERING SURVEYING  
137 SOUTH WASHINGTON STREET  
OHIO 44883  
(419) 447-4300JOB NO. 91084-S  
(363)DRAWN BY: DJN  
08 - 91  
CHECKED BY: JCH  
08-08-91  
REVISIONS: 1/1  
SHEET NO. 1/1FRED SCHECK, et al  
103 - 205

5.514 ACRES

SURVEY NO. 9151  
VOL 7 PAGE 185  
DATE Aug. 15, 1991NOTE: ALL IRON ROD SET ARE 1/2" DIA. WITH  
PERSONALIZED CAPS (HANK # 6972)  
DRIVEN FLUSH.

## LEGEND

| SET | FOUND | DESCRIPTION    |
|-----|-------|----------------|
| △   | ▲     | STONE          |
| □   | ■     | MONUMENT BOX   |
| ⊕   | ⊙     | CONC. MONUMENT |
| ⊗   | ⊘     | RAILROAD SPIKE |
| ○   | ●     | NAIL           |
| ○   | ●     | IRON ROD       |
| ○   | ●     | IRON PIPE      |
| ○   | ●     | DRILL HOLE     |
| ○   | ■     | WOOD POST      |
| D   |       | DEED           |
| P   |       | PLAT           |
| M   |       | MEASURED       |
| S   |       | SURVEYED       |
| C   |       | CALCULATED     |

I HEREBY DECLARE THAT THE ABOVE PARCEL WAS  
SURVEYED DURING JULY, 1991  
PROPERTY LINES SHOWN ARE LOCATED FROM DEEDS  
ON RECORD AND ARE DEED LINES. BEARINGS ARE  
ASSUMED FOR ANGULAR MEASUREMENT ONLY. ALL  
INFORMATION SHOWN IS TRUE AND CORRECT TO THE  
BEST OF MY KNOWLEDGE AND BELIEF.James G. Homan, Jr., P.S. # 6972  
DATE