

LEGEND

- Ø SET 1/2" HEAD METAL NAIL
 - 1/2" IRON PIPE SET WITH CAP 5647
 - ⊗ STONE WITH RAILROAD SPIKE OVER
- REF.SURVEY BOOK D PG.183
WYANDOT CO. STONE RECORD

SURVEY NUMBER: 08-64
VOLUME: B PAGE: 139
DATE FILED: 8-20-08
PARCEL #: 20-0720-0000

ASSUMED
NORTH

0 100 200
1 INCH = 100 FEET

THE BASIS OF BEARING
IS BASED ON THE
ASSUMED HALF
SECTION LINE
BEARING AND ALL
OTHER BEARINGS
ARE FROM ANGLES
AND DISTANCES
MEASURED IN
THE FIELD.

RICHARD R. MILLER ETUX
D.V. 134 PG. 552

N.0° 36' 30 "W.
435.61 FT. NAIL TO P.

N. 89° 29' 39" E.
200.00 FT.


2.000 ACRES

B.

EAST SECTION LINE

DANNY & PHYLLIS LUIKART
D.V. 187 PG. 727

S.0° 36' 30" E.
435.61 FT. P. TO STONE



I HEREBY CERTIFY THE ABOVE PLAT IS TRUE
AND CORRECT ACCORDING TO A SURVEY,

MADE IN JULY 31, 2008

OHIO REGISTERED SURVEYOR NO 5647

BY Jerry B. Weininger
JERRY B. WEININGER

E.-- W. HALF SECTION LINE AND C/L S. R. 294
60' R/W

30 FT.

200.00 FT.

EAST 1/4 POST
SECTION 31

P. O. B.

S.89° 29' 39" W. ASSUMED

PART NORTHEAST QUARTER
SECTION 31 T. 3 S. R. 13 E.

TWP: MIFFLIN
COUNTY: WYANDOT ,OHIO

SURVEY FOR:
RICHARD MILLER

J.B.W.
6569 C. H. 2 MCCUTCHENVILLE
OHIO 44844 186

DATE: JULY 31 , 2008
SCALE: 1 INCH = 100 FEET

ALL REGIONAL PLANNING
REQUIREMENTS HAVE BEEN
APPROVED FOR THIS SURVEY
APPLICATION # 08-31