

ROBERT RALL
 D.V. 364 P. 587

4" x 6" WOOD POST
 EAST-WEST QUARTER SECTION LINE
 N 89° 05' 12" E 500.00' (C)
 8" WOOD POST
 N 1/8 POST
 SE 1/4 SECTION 18
 P.O.B.

5' x 30' FENCED AREA (TYPICAL)
 200'
 200'
 GUYED WIRES (TYP)
3.739 ACRES
 50' x 50' FENCED AREA
 15' x 30' BUILDING
 CENTER OF TOWER
 ELEVATION: 872'
 LATITUDE: 40° 46' 52"
 LONGITUDE: 83° 17' 20"
 DETERMINED BY SCALING U.S.G.S. QUADRANGLE MAP
 200'
 200'
 ACCESS ROAD
 30.00' 00"
 S 89° 05' 12" W 500.00' (C)
 GUY ANDERS (TYPICAL)
 30.00' 00"
 S 00° 00' 00" W (ASSUMED) 500.00' (C)
 COUNTY HIGHWAY 115 80' R/W
 2" 1/8 POST
 SE 1/4 SECTION 18
 STONE IN
 MON. BOX

RON NEVELL
 D.V. 178 P. 1071

SURVEY NUMBER: 9748
 VOLUME: C, PAGE: 70
 FILING DATE: 10-26-97

C.H.



1" = 50'

SCALE FEET

REFERENCES

DEED VOLUME AND PAGE AS SHOWN

WYANDOT COUNTY CORNERSTONE REFERENCES

NOTE: ALL IRON ROD SET ARE 1/2" DIA. WITH
PERSONALIZED CAPS (HANK # 6972)
DRIVEN FLUSH.

SET	FOUND	DESCRIPTION
		STONE
		MONUMENT BOX
		CONC. MONUMENT
		RAILROAD SPIKE
		NAIL
		IRON ROD
		IRON PIPE
		DRILL HOLE
		WOOD POST
	D	DEED
	P	PLAT
	M	MEASURED
	S	SURVEYED
	C	CALCULATED

I HEREBY DECLARE THAT THE ABOVE PARCEL WAS
SURVEYED DURING OCTOBER, 1991
PROPERTY LINES SHOWN ARE LOCATED FROM DEEDS
ON RECORD AND ARE DEED LINES. BEARINGS ARE
ASSUMED FOR ANGULAR MEASUREMENT ONLY. ALL
INFORMATION SHOWN IS TRUE AND CORRECT TO THE
BEST OF MY KNOWLEDGE AND BELIEF.



James G. Homan
JAMES G. HOMAN, JR., P.S.# 6972 DATE 04-15-92

HANK AND ASSOCIATES, INC.

SURVEY FOR **PAUL BLANKER**
LOCATED IN THE SE, 1/4 OF SECTION 18,
PITT TOWNSHIP, T-3-S, R-14-E,
WYANDOT COUNTY, OHIO

DRAWN BY:	CHECKED:
DJN 10-91	JCH 02/15/92

REVISIONS

DATE	BY	REVISIONS
10-1-71	W. H. H. H.	1. H. H. H.

SHEET NO. 1/1