

LINE	BEARING	DISTANCE
L1	N 00°38'01" E	41.50'

Distances shown hereon are expressed in feet and decimal parts thereof.

Bearings are to an assumed meridian and are used to express angles only.

CERTIFICATION: I hereby state that the foregoing survey was prepared from actual field measurements, in accordance with Chapter 4733-37, Ohio Administrative Code.

By: Nathaniel B. Ramsey, P.S. #8396
For Ramsey Surveying

06/19/2025
Date



SURVEY NUMBER: 25-45
VOLUME: B PAGE: 308
DATE FILED: 9-17-2025
PARCEL #: 02-1100-0000


ALL REGIONAL PLANNING
REQUIREMENTS HAVE BEEN
APPROVED FOR THIS SURVEY
APPLICATION # _____

REFERENCE DOCUMENTS

SURVEY BY VICTOR B. KOEHLER, VOL. C, PG. 1272
SURVEY BY VICTOR B. KOEHLER, VOL. C, PG. 1283
SURVEY BY VICTOR B. KOEHLER, VOL. C, PG. 957
SURVEY BY JACQUES M. GLAZE, VOL. B, PG. 69
PERTINENT DEEDS

LEGEND

- Ø IRON PIPE FOUND
- ⊗ SURVEY SPIKE FOUND
- IRON PIN FOUND
- △ MAGNAIL SPIKE FOUND
- IRON PIN SET-5/8" REBAR
SET WITH I.D. CAP STAMPED
"RAMSEY S-8396"
- ✕ MAGNAIL SPIKE SET



RAMSEY SURVEYING
Professional Land Surveying Services

283 Eby Road
Shiloh, Ohio 44878
TEL (419) 512-2596 FAX (419) 522-0399
EMAIL nramsey@ramsey-surveying.com

**SURVEY MADE FOR PROPERTY
TRANSFER**

**PART OF THE SOUTHWEST QUARTER
OF SECTION 9, ANTRIM TOWNSHIP
T-3 S, R-15 E
WYANDOT COUNTY, OHIO**

DRAWN HCO	CHECKED NBR	SCALE 1" = 150'	DATE 06/19/2025
DWG NO: SM-6210_A_PG	JOB NO: SM-6210	SHEET 1 OF 1	